



NOMINAL BORE	TOTAL LENGTH (+/-5mm)	BELLOWS	
		BELLOWS	A
mm	L		
15	300	27	140
20	300	27	140
25	300	27	140
32	350	26	180
40	350	24	180
50	350	24	180
65	350	14	140
80	350	14	140
100	350	12	145
125	350	12	145
150	350	12	145
200	350	10	140

Model - SSEJ-250CW-SG-ES

WELD ENDS - SCHEDULE 40 PIPE

FOR TIE RODS ADD "SG" SUFFIX

FOR EXTERNAL SHROUD ADD "ES" SUFFIX

WORKING PRESSURE : 16 bar

WORKING TEMPERATURE : -50°C to +450°C

AXIAL MOVEMENT : + / - 25mm



■ CONSTRUCTION		
ITEM	PARTS	MATERIAL
1	BELLOWS	SS304 (2 PLY)
2	FEMALE ENDS	COPPER
3	GUSSET	CARBON STEEL
4	TIE RODS	CARBON STEEL
5	INNER SLEEVE	SS304
6	END PIPE	SS304
7	EXTERNAL COVER	CARBON STEEL

STANDARD FINISH
 FLANGES / GUSSETS: GALVO PAINT
 CONTROL ROD & HARDWARE : ZINC PLATED